

Freedom

FH Series

AUX-09/12/18/24FH



Model		AUX-09FH	AUX-12FH	AUX-18FH	AUX-24FH
Cooling & Heating capacity	[kW]	2,60 / 2,80	3,50 / 3,50	5,00 / 5,50	6,50 / 6,50
SEER/SCOP	[W/W]	6,5 / 4,37	6,65 / 4,36	6,57 / 4,02	6,89 / 4,11
Energy Efficiency Class	-	A++ / A+	A++ / A+	A++ / A+	A++ / A+
Indoor unit		AUX-09FH/I	AUX-12FH/I	AUX-18FH/I	AUX-24FH/I
Sound pressure level	[dB(A)]	32/29/26/22/20	34/30/28/23/20	40/32/29/26/22	38/35/32/30/23
Indoor unit dimensions W/H/D	[mm]	750 x 285 x 200	750 x 285 x 200	900 x 310 x 225	1082 x 330 x 233
Indoor unit weight	[kg]	7,5	8,0	12,0	15,0
Outdoor unit		AUX-09FH/O	AUX-12FH/O	AUX-18FH/O	AUX-24FH/O
Refrigerant type	-	R32	R32	R32	R32
Sound pressure level	[dB(A)]	40	42	43	43
Outdoor unit dimensions W/H/D	[mm]	730 x 545 x 285	730 x 545 x 285	800 x 545 x 315	900 x 700 x 350
Outdoor unit weight	[kg]	25,0	25,0	35,0	45,0
Application area	[°C]	-10 / -15	-10 / -15	-10 / -15	-10 / -15

Air conditioning equipment contains fluorinated greenhouse gases R32.
Specifications, appearance and functions are subject to change without prior notice.



R32 refrigerant	DC inverter	Built-in Wi-Fi module	Auto restart	TURBO mode	Fast cooling / heating	Timer	Self-cleaning	Sleep mode	Intelligent defrosting	Honeycomb filter	Antibacterial filter
Air ionizer	LED display	I FEEL function	Anti-Cold-Air function	Anti-Fungus function	Two-way draining	Paddles made of hydrophilic aluminum	Vertical airflow	Horizontal airflow	4D air supply	Self-diagnosis function	Standby 0.3 W
Anti-corrosion coated casings (outdoor units)	Strong dehumidification	Super EMC	Wireless remote controller	Cooling mode	Heating mode	Fan mode	Dry mode	Auto mode	Optional air filters		

