

# Halo Deluxe

## HE Series

AUX-09/12/18/24HE



Model		AUX-09HE	AUX-12HE	AUX-18HE	AUX-24HE
<b>Cooling &amp; Heating capacity</b>	[kW]	2,75 / 3,10	3,60 / 3,80	5,50 / 5,90	7,30 / 7,30
<b>SEER/SCOP</b>	[W/W]	6,16 / 4,17	6,12 / 4,14	6,57 / 4,02	6,89 / 4,11
<b>Energy Efficiency Class</b>	-	A++ / A+	A++ / A+	A++ / A+	A++ / A+
Indoor unit		AUX-09HE/I	AUX-12HE/I	AUX-18HE/I	AUX-24HE/I
<b>Sound pressure level</b>	[dB(A)]	38/31/27/22/19	38/32/29/23/20	41/32/31/26/23	38/36/33/31/23
<b>Indoor unit dimensions W/H/D</b>	[mm]	788 x 292 x 198	788 x 292 x 198	940 x 316 x 224	1121 x 329 x 231
<b>Indoor unit weight</b>	[kg]	8,0	8,5	12,0	14,0
Outdoor unit		AUX-09HE/O	AUX-12HE/O	AUX-18HE/O	AUX-24HE/O
<b>Refrigerant type</b>	-	R32	R32	R32	R32
<b>Sound pressure level</b>	[dB(A)]	40	42	44	45
<b>Outdoor unit dimensions W/H/D</b>	[mm]	730 x 545 x 285	730 x 545 x 285	800 x 545 x 315	900 x 700 x 350
<b>Outdoor unit weight</b>	[kg]	25,0	25,0	35,0	45,0
<b>Application area</b>	[°C]	-10 / -15	-10 / -15	-10 / -15	-10 / -15

Air conditioning equipment contains fluorinated greenhouse gases R32.  
Specifications, appearance and functions are subject to change without prior notice.



R32 refrigerant	DC inverter	Built-in Wi-Fi module	Auto restart	TURBO mode	Timer	Self-cleaning	Self-diagnosis function	Sleep mode	Intelligent defrosting	Increased density filter	PM2,5 filter
Antibacterial filter	Air ionizer	LED display	Gold-plated fins of the heat exchanger	Gold-plated fins of the heat exchanger	Super EMC	Paddles made of hydrophilic aluminum	Two-way draining	I FEEL function	Anti-Cold-Air function	Anti-Fungus function	Standby 0,3W
ECO mode	Vertical airflow	Horizontal airflow	4D air supply	Anti-corrosion coated casings (outdoor units)	Wireless remote controller	COOLING	HEATING	VENTILATION	DRY MODE	AUTO	Optional air filters

