

J-Smart

J20 Series

AUX-09/12/18/24J20



Model		AUX-09J20	AUX-12J20	AUX-18J20	AUX-24J20
Cooling & Heating capacity	[kW]	2,70 / 3,00	3,60 / 3,70	5,40 / 5,80	7,20 / 7,20
SEER/SCOP	[W/W]	6,16 / 4,17	6,12 / 4,14	6,57 / 4,02	6,89 / 4,11
Energy Efficiency Class	-	A++ / A+	A++ / A+	A++ / A+	A++ / A+
Indoor unit		AUX-09J20/I	AUX-12J20/I	AUX-18J20/I	AUX-24J20/I
Sound pressure level	[dB(A)]	38/31/27/22/19	38/32/29/23/20	41/32/31/26/23	38/36/33/31/23
Indoor unit dimensions W/H/D	[mm]	792 x 292 x 201	792 x 292 x 201	940 x 316 x 224	1132 x 330 x 232
Indoor unit weight	[kg]	8,0	8,5	12,0	15,0
Outdoor unit		AUX-09J20/O	AUX-12J20/O	AUX-18J20/O	AUX-24J20/O
Refrigerant type	-	R32	R32	R32	R32
Sound pressure level	[dB(A)]	40	42	44	45
Outdoor unit dimensions W/H/D	[mm]	730 x 545 x 285	730 x 545 x 285	800 x 545 x 315	900 x 700 x 350
Outdoor unit weight	[kg]	25,0	25,0	35,0	45,0
Application area	[°C]	-10 / -20	-10 / -20	-10 / -20	-10 / -20

Air conditioning equipment contains fluorinated greenhouse gases R32.
Specifications, appearance and functions are subject to change without prior notice.



R32 refrigerant

DC inverter

Built-in Wi-Fi module

Auto restart

TURBO mode

Timer

Self-cleaning

Self-diagnosis function

Sleep mode

Intelligent defrosting

Increased density filter

PM2.5 filter

Antibacterial filter

Air ionizer

LED display

Gold-plated fins of the heat exchanger

Gold-plated fins of the heat exchanger

Super EMC

Paddles made of hydrophilic aluminum

Two-way draining

I FEEL function

Anti-Cold-Air function

Anti-Fungus function

Standby 0,3W

ECO mode

Vertical airflow

Horizontal airflow

4D air supply

Easy and fast installation

Drip tray heater (outdoor unit)

Anti-corrosion coated casings (outdoor units)

Wireless remote controller

COOLING

HEATING

VENTILATION

DRY MODE

AUTO mode

Optional air filters

