

# Multi Split Outdoor Unit

AUX-M2-(14/18)LCLH, AUX-M3-(21/27)LCLH, AUX-M4-36LCLH, AUX-M5-42LCLH



Indoor unit model		AUX-M2-14LCLH	AUX-M2-18LCLH	AUX-M3-21LCLH
Maximum number of indoor units	-	2	2	3
Cooling capacity	[kW]	4,1 (1,8 - 4,51)	5,3 (2,0 - 5,83)	6,2 (2,2 - 6,71)
Heating capacity	[kW]	4,8 (2,05 - 5,28)	5,6 (2,21 - 6,16)	6,6 (2,39 - 7,26)
Power	[V~,Hz,Ph]	220-240, 50, 1	220-240, 50, 1	220-240, 50, 1
Energy Efficiency Class (cooling/heating)	-	A++ / A+	A++ / A+	A++ / A+
SEER / SCOP	[W/W]	6,16 / 4,06	7,07 / 4,08	6,57 / 4,38
Sound pressure level	[dB(A)]	54	55	56
Indoor unit dimensions W/H/D	[mm]	800 x 315 x 545	800 x 315 x 545	834 x 328 x 655
Indoor unit weight	[kg]	34,0	36,0	44,0
Refrigerant type	-	R32	R32	R32
Application area (cooling/heating)	[°C]	-15~52 / -20~24	-15~52 / -20~24	-15~52 / -20~24
Total installation length	[m]	40	40	60
Maximum distance between the indoor and the outdoor units	[m]	25	25	30
Maximum height difference between an indoor and outdoor unit	[m]	15	15	15
Maximum height difference between indoor units	[m]	10	10	10

Indoor unit model		AUX-M3-27LCLH	AUX-M4-36LCLH	AUX-M5-42LCLH
Maximum number of indoor units	-	3	4	5
Cooling capacity	[kW]	7,90 (2,3 - 8,69)	10,50 (2,5 - 11,0)	12,00 (2,77 - 12,7)
Heating capacity	[kW]	8,20 (2,45 - 9,02)	11,00 (2,67 - 11,2)	13,00 (2,96 - 13,1)
Power	[V~,Hz,Ph]	220-240, 50, 1	220-240, 50, 1	220-240, 50, 1
Energy Efficiency Class (cooling/heating)	-	A++ / A+	A++ / A+	A++ / A+
SEER / SCOP	[W/W]	6,30 / 4,04	6,10 / 4,00	6,10 / 4,10
Sound pressure level	[dB(A)]	58	61	61
Indoor unit dimensions W/H/D	[mm]	834 x 328 x 655	985 x 395 x 808	985 x 395 x 808
Indoor unit weight	[kg]	46,0	74,0	75,0
Refrigerant type	-	R32	R32	R32
Application area (cooling/heating)	[°C]	-15~52 / -20~24	-15~52 / -20~24	-15~52 / -20~24
Total installation length	[m]	60	80	80
Maximum distance between the indoor and the outdoor units	[m]	30	35	35
Maximum height difference between an indoor and outdoor unit	[m]	15	15	15
Maximum height difference between indoor units	[m]	10	10	10

Air conditioning equipment contains fluorinated greenhouse gases R32.

Specifications, appearance and functions are subject to change without prior notice.

