

Q-Smart

QC Series

AUX-09/12/18/24QC



Model		AUX-09QC	AUX-12QC	AUX-18QC	AUX-24QC
Cooling & Heating capacity	[kW]	2,7 / 3,0	3,5 / 3,8	5,4 / 5,6	6,7 / 7,2
SEER/SCOP	[W/W]	6,1 / 4,00	6,1 / 4,00	7,3 / 4,3	6,1 / 4,00
Energy Efficiency Class	-	A++ / A+	A++ / A+	A++ / A+	A++ / A+
Indoor unit		AUX-09QC/I	AUX-12QC/I	AUX-18QC/I	AUX-24QC/I
Sound pressure level	[dB(A)]	38/31/27/22/19	38/32/29/23/20	41/32/31/26/23	38/36/33/31/23
Indoor unit dimensions W/H/D	[mm]	761 x 295 x 200	761 x 295 x 200	960 x 316 x 312	1090 x 328 x 227
Indoor unit weight	[kg]	7,5	7,5	11,0	12,5
Outdoor unit		AUX-09QC/O	AUX-12QC/O	AUX-18QC/O	AUX-24QC/O
Refrigerant type	-	R32	R32	R32	R32
Sound pressure level	[dB(A)]	40	42	44	45
Outdoor unit dimensions W/H/D	[mm]	705 x 530 x 279	705 x 530 x 279	785 x 530 x 300	900 x 700 x 350
Outdoor unit weight	[kg]	22,5	22,5	28	39
Application area	[°C]	-10 / -15	-10 / -15	-10 / -15	-10 / -15

Air conditioning equipment contains fluorinated greenhouse gases R32.
Specifications, appearance and functions are subject to change without prior notice.



- R32 refrigerant
- DC inverter
- Built-in Wi-Fi module
- Auto restart
- TURBO mode
- Fast cooling / heating
- Timer
- Self-cleaning
- Sleep mode
- Intelligent defrosting
- Increased density filter
- Antibacterial filter
- Air ionizer
- LED display
- I FEEL function
- Anti-Cold-Air function
- Anti-Fungus function
- Two-way draining
- Paddles made of hydrophilic aluminum
- Vertical airflow
- Horizontal airflow
- 4D air supply
- Self-diagnosis function
- Standby 0.3 W
- Anti-corrosion coated casings (outdoor units)
- Strong dehumidification
- Super EMC
- Wireless remote controller
- COOLING
- HEATING
- FAN MODE
- DRY MODE
- AUTO
- Optional air filters

