

Modell		SEV-12CAC	SEV-18CAC	SEV-24CAC	SEV-36CAC
Kühlleistung	[kW]	3,60 (1,35 - 4,40)	5,00 (1,53 - 5,60)	7,00 (2,16 - 8,20)	10,55 (2,90 - 13,00)
	[Btu/h]	12000 (4600 - 15)	18000 (200 - 100)	24000 (400 - 280)	36000 (-44300)
Heizleistung	[kW]	4,20 (1,24 - 5,30)	5,60 (1,40 - 6,20)	8,00 (1,98 - 9,30)	11,15 (2,60 - 13,50)
	[Btu/h]	14300 (4200 - 18100)	19100 (4800 - 00)	27300 (6 00)	38000 (88)
Stromanschluss	[V,Hz,Ph]	220-240, 50, 1	220-240, 50, 1	220-240, 50, 1	220-240, 50, 1
SEER	[W/W]	6,2	6,3	6,5	6,1
SCOP	[W/W]	4,1	4,0	4,2	4,0
Energieeffizienz	[-]	A++ / A+	A++ / A+	A++ / A+	A++ / A+
<b>Inneneinheit</b>	[-]	<b>SEV-12CAC</b>	<b>SEV-18CAC</b>	<b>SEV-24CAC</b>	<b>SEV-36CAC</b>
Luftvolumenstrom	[m³/h]	700/600/530	700/600/530	1300/1050/950	1800/1550/1350
Schalldruckpegel	[dB(A)]	45/44/36	45/44/36	47/43/38	51/48/45
Schalleistungspegel	[dB(A)]	56	56	57	62
Abmessungen	[mm]	570x570x260	570x570x260	835x835x250	835x835x290
Blende Abmessungen	[mm]	650x650x55	650x650x55	950x950x55	950x950x55
Gewicht (netto/brutto)	[kg]	17 / 20	17 / 20	24 / 27,5	26,5 / 30,5
Blende Gewicht (netto/brutto)	[kg]	2,2 / 3,7	2,2 / 3,7	5,3 / 7,8	5,3 / 7,8
Kondensat	[mm(zoll)]	DN20 (R3/4)	DN20 (R3/4)	DN20 (R3/4)	DN20 (R3/4)
<b>Außeneinheit</b>		<b>SEV-12CAO</b>	<b>SEV-18CAO</b>	<b>SEV-24CAO</b>	<b>SEV-36CAO</b>
Luftvolumenstrom	[m³/h]	2600	2600	3750	4000
Schalldruckpegel	[dB(A)]	54	55	58	57
Schalleistungspegel	[dB(A)]	64	64	67	66
Abmessungen	[mm]	800x315x545	800x315x545	900x350x700	970x395x805
Gewicht netto/brutto	[kg]	35 / 38	37 / 40	51 / 55	72 / 76
Rohranschlüsse	Flüssig	[mm(zoll)]	6,35 (1/4)	6,35 (1/4)	9,52 (3/8)
	Gas	[mm(zoll)]	12,7 (1/2)	12,7 (1/2)	15,88 (5/8)
Max. Einbaulänge	[m]	25	30	50	65
Max. Höhenunterschied	[m]	10	20	25	30

Modell		SEV-42CAC	SEV-48CAC	SEV-60CAC
Kühlleistung	[kW]	12,10 (2,90 - 13,50)	14,00 (4,76 - 16,50)	16,00 (4,76 - 17,50)
	[Btu/h]	42000 (9800 - 46000)	48000 (16241 - 56298)	55000 (16241 - 59710)
Heizleistung	[kW]	13,50 (2,60 - 15,00)	16,00 (4,78 - 16,15)	17,00 (4,78 - 18,50)
	[Btu/h]	46000 (8800 - 51100)	55000 (16309 - 55104)	58000 (16308 - 63122)
Stromanschluss	[V,Hz,Ph]	220-240, 50, 1	380-415, 50, 3	380-415, 50, 3
SEER	[W/W]	6,1	6,1	6,1
SCOP	[W/W]	4,0	4,0	4,0
Energieeffizienz	[-]	A++ / A+	A++ / A+	A++ / A+
<b>Inneneinheit</b>	[-]	<b>SEV-42CAC</b>	<b>SEV-48CAC</b>	<b>SEV-60CAC</b>
Luftvolumenstrom	[m³/h]	1800/1550/1350	1950/1750/1500	1950/1750/1500
Schalldruckpegel	[dB(A)]	51/48/45	52/50/48	52/50/48
Schalleistungspegel	[dB(A)]	62	65	65
Abmessungen	[mm]	835x835x290	835x835x290	835x835x290
Blende Abmessungen	[mm]	950x950x55	950x950x55	950x950x55
Gewicht netto/brutto	[kg]	26,5 / 30,5	31 / 35	31 / 35
Blende Gewicht netto/brutto	[kg]	5,3 / 7,8	5,3 / 7,8	5,3 / 7,8
Kondensat	[mm(zoll)]	DN20 (R3/4)	DN20 (R3/4)	DN20 (R3/4)
<b>Außeneinheit</b>		<b>SEV-42CAO</b>	<b>SEV-48CAO</b>	<b>SEV-60CAO</b>
Luftvolumenstrom	[m³/h]	4200	7200	7200
Schalldruckpegel	[dB(A)]	57	60	60
Schalleistungspegel	[dB(A)]	66	70	70
Abmessungen	[mm]	970x395x805	940x370x1325	940x370x1325
Gewicht netto/brutto	[kg]	72 / 76	92 / 102	92 / 102
Rohranschlüsse	Flüssig	[mm(zoll)]	9,52 (3/8)	9,52 (3/8)
	Gas	[mm(zoll)]	15,88 (5/8)	19,05 (3/4)
Max. Einbaulänge	[m]	65	65	65
Max. Höhenunterschied	[m]	30	30	30