

Modell		SEV-18CAD	SEV-24CAD	SEV-36CAD
Kühlleistung	[kW]	5,00 (1,53 - 5,60)	7,00 (2,16 - 8,20)	10,55 (2,90 - 13,00)
	[Btu/h]	18000 (5200 - 19100)	24000 (7400 - 28000)	36000 (9800 - 44300)
Heizleistung	[kW]	5,60 (1,40 - 6,20)	8,00 (1,98 - 9,30)	11,15 (2,60 - 13,50)
	[Btu/h]	19100 (4800 - 21200)	27300 (6800 - 31700)	38000 (8800 - 46000)
Stromanschluss	[V,Hz,Ph]	220-240, 50, 1	220-240, 50, 1	220-240, 50, 1
SEER	[W/W]	6,2	6,1	6,1
SCOP	[W/W]	4,0	4,0	4,1
Energieeffizienz	[-]	A++ / A+	A++ / A+	A++ / A+
Inneneinheit	[-]	SEV-18CAD	SEV-24CAD	SEV-36CAD
Luftvolumenstrom	[m³/h]	1150/960/840	1400/1190/980	1900/1600/1400
Schalldruckpegel	[dB(A)]	43/41/40	44/41/39	44/41/39
Schalleistungspegel	[dB(A)]	53	55	55
Abmessungen	[mm]	1000x700x245	1000x700x245	1400x700x245
Gewicht netto/brutto	[kg]	31 / 37	32 / 38	42 / 48
Kondensat	[mm(zoll)]	DN20 (R3/4)	DN20 (R3/4)	DN20 (R3/4)
Außeneinheit		SEV-18CAO	SEV-24CAO	SEV-36CAO
Luftvolumenstrom	[m³/h]	2600	3750	4000
Schalldruckpegel	[dB(A)]	55	58	57
Schalleistungspegel	[dB(A)]	64	67	66
Abmessungen	[mm]	800x315x545	900x350x700	970x395x805
Gewicht netto/brutto	[kg]	37 / 40	51 / 55	72 / 76
Rohranschlüsse	Flüssig [mm(zoll)]	6,35 (1/4)	9,52 (3/8)	9,52 (3/8)
	Gas [mm(zoll)]	12,7 (1/2)	15,88 (5/8)	15,88 (5/8)
Max. Einbaulänge	[m]	30	50	65
Max. Höhenunterschied	[m]	20	25	30

Modell		SEV-42CAD	SEV-48CAD	SEV-60CAD
Kühlleistung	[kW]	12,10 (2,90 - 13,50)	14,00 (4,76 - 16,50)	16,00 (4,76 - 17,50)
	[Btu/h]	42000 (9800 - 46000)	48000 (16241 - 56298)	55000 (16241 - 59710)
Heizleistung	[kW]	13,50 (2,60 - 15,00)	16,00 (4,78 - 16,15)	17,00 (4,78-18,50)
	[Btu/h]	46000 (8800 - 51100)	55000 (16309 - 55104)	58000 (16308 - 63122)
Stromanschluss	[V,Hz,Ph]	220-240, 50, 1	380-415, 50, 3	380-415, 50, 3
SEER	[W/W]	6,1	6,1	6,1
SCOP	[W/W]	4,1	4,0	4,0
Energieeffizienz	[-]	A++ / A+	A++ / A+	A++ / A+
Inneneinheit	[-]	SEV-42CAD	SEV-48CAD	SEV-60CAD
Luftvolumenstrom	[m³/h]	1900/1600/1400	2300/2000/1700	2300/2000/1700
Schalldruckpegel	[dB(A)]	44/41/39	52/49/47	52/49/47
Schalleistungspegel	[dB(A)]	55	64	64
Abmessungen	[mm]	1400x700x245	1400x700x245	1400x700x245
Gewicht netto/brutto	[kg]	42 / 48	42 / 48	42 / 48
Kondensat	[mm(zoll)]	DN20 (R3/4)	DN20 (R3/4)	DN20 (R3/4)
Außeneinheit		SEV-42CAO	SEV-48CAO	SEV-60CAO
Luftvolumenstrom	[m³/h]	4200	7200	7200
Schalldruckpegel	[dB(A)]	57	60	60
Schalleistungspegel	[dB(A)]	66	70	70
Abmessungen	[mm]	970x395x805	940x370x1325	940x370x1325
Gewicht netto/brutto	[kg]	72 / 76	92 / 102	92 / 102
Rohranschlüsse	Flüssig [mm(zoll)]	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)
	Gas [mm(zoll)]	15,88 (5/8)	19,05 (3/4)	19,05 (3/4)
Max. Einbaulänge	[m]	65	65	65
Max. Höhenunterschied	[m]	30	30	30