

Modell		SEV-18CAF	SEV-24CAF	SEV-36CAF
Kühlleistung	[kW]	5,00 (1,53 - 5,60)	7,00 (2,16 - 8,20)	10,55 (2,90 - 13,00)
	[Btu/h]	18000 (5200 - 19100)	24000 (7400 - 28000)	36000 (9800 - 44300)
Heizleistung	[kW]	5,60 (1,40 - 6,20)	8,00 (1,98 - 9,30)	11,15 (2,60 - 13,50)
	[Btu/h]	19100 (4800 - 21200)	27300 (6800 - 31700)	38000 (8800 - 46000)
Stromanschluss	[V,Hz,Ph]	220-240, 50, 1	220-240, 50, 1	220-240, 50, 1
SEER	[W/W]	6,1	6,3	6,1
SCOP	[W/W]	4,1	4,1	4,0
Energieeffizienz	[-]	A++ / A+	A++ / A+	A++ / A+
<b>Inneneinheit</b>	[-]	<b>SEV-18CAF</b>	<b>SEV-24CAF</b>	<b>SEV-36CAF</b>
Luftvolumenstrom	[m³/h]	900/730/650	1300/1052/920	1800/1550/1350
Schalldruckpegel	[dB(A)]	45/40/34	47/43/38	53/50/47
Schalleistungspegel	[dB(A)]	56	57	63
Abmessungen	[mm]	929x660x205	1280x660x205	1631x660x205
Gewicht netto/brutto	[kg]	25 / 28	32 / 38	44 / 50
Kondensat	[mm(zoll)]	DN20 (R3/4)	DN20 (R3/4)	DN20 (R3/4)
<b>Außeneinheit</b>		<b>SEV-18CAO</b>	<b>SEV-24CAO</b>	<b>SEV-36CAO</b>
Luftvolumenstrom	[m³/h]	2600	3750	4000
Schalldruckpegel	[dB(A)]	55	58	57
Schalleistungspegel	[dB(A)]	64	67	66
Abmessungen	[mm]	800x315x545	900x350x700	970x395x805
Gewicht netto/brutto	[kg]	37 / 40	51 / 55	72 / 76
Rohranschlüsse	Flüssig [mm(zoll)]	6,35 (1/4)	9,52 (3/8)	9,52 (3/8)
	Gas [mm(zoll)]	12,7 (1/2)	15,88 (5/8)	15,88 (5/8)
Max. Einbaulänge	[m]	30	50	65
Max. Höhenunterschied	[m]	20	25	30

Modell		SEV-42CAF	SEV-48CAF	SEV-60CAF
Kühlleistung	[kW]	12,10 (2,90 - 13,50)	14,00 (4,76 - 16,50)	16,00 (4,76 - 17,50)
	[Btu/h]	42000 (9800 - 46000)	48000 (16241 - 56298)	55000 (16241 - 59710)
Heizleistung	[kW]	13,50 (2,60 - 15,00)	16,00 (4,78 - 16,15)	17,00 (4,78 - 18,50)
	[Btu/h]	46000 (8800 - 51100)	55000 (16309 - 55104)	58000 (16308 - 63122)
Stromanschluss	[V,Hz,Ph]	220-240, 50, 1	380-415, 50, 3	380-415, 50, 3
SEER	[W/W]	6,1	6,1	6,1
SCOP	[W/W]	4,0	4,0	4,0
Energieeffizienz	[-]	A++ / A+	A++ / A+	A++ / A+
<b>Inneneinheit</b>	[-]	<b>SEV-42CAF</b>	<b>SEV-48CAF</b>	<b>SEV-60CAF</b>
Luftvolumenstrom	[m³/h]	1800/1550/1350	1900/1600/1400	1900/1600/1400
Schalldruckpegel	[dB(A)]	53/50/47	53/51/49	53/51/49
Schalleistungspegel	[dB(A)]	63	64	64
Abmessungen	[mm]	1631x660x205	1631x660x205	1631x660x205
Gewicht netto/brutto	[kg]	44 / 50	44 / 50	44 / 50
Kondensat	[mm(zoll)]	DN20 (R3/4)	DN20 (R3/4)	DN20 (R3/4)
<b>Außeneinheit</b>		<b>SEV-42CAO</b>	<b>SEV-48CAO</b>	<b>SEV-60CAO</b>
Luftvolumenstrom	[m³/h]	4200	7200	7200
Schalldruckpegel	[dB(A)]	57	60	60
Schalleistungspegel	[dB(A)]	66	70	70
Abmessungen	[mm]	970x395x805	940x370x1325	940x370x1325
Gewicht netto/brutto	[kg]	72 / 76	92 / 102	92 / 102
Rohranschlüsse	Flüssig [mm(zoll)]	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)
	Gas [mm(zoll)]	15,88 (5/8)	19,05 (3/4)	19,05 (3/4)
Max. Einbaulänge	[m]	65	65	65
Max. Höhenunterschied	[m]	30	30	30