

Modell		SEV-2M14	SEV-2M18	SEV-3M21
Kühlleistung	[kW]	4,1 (1,8 - 4,51)	5,3 (2,0 - 5,83)	6,2 (2,2 - 6,71)
	[Btu/h]	13989 (6142 - 15388)	18084 (6824 - 19892)	21154 (7506 - 22895)
Heizleistung	[kW]	4,8 (2,05 - 5,28)	5,6 (2,21 - 6,16)	6,6 (2,39 - 7,26)
	[Btu/h]	16378 (6995 - 18015)	19107 (7541 - 21017)	22519 (8155 - 24771)
Stromanschluss		[V,H,z,Ph]	220-240, 50, 1	220-240, 50, 1
Energieverbrauch	Kühlen [W]	1240	1750	1920
	Heizen [W]	1150	1540	1780
Stromverbrauch	Kühlen [A]	5,4	7,6	8,3
	Heizen [A]	5,0	6,7	7,8
SEER		[W/W]	6,16	7,07
SCOP		[W/W]	4,06	4,08
Energieeffizienz	Kühlen [-]	A++	A++	A++
	Heizen [-]	A+	A+	A+
Luftvolumenstrom		[m³/h]	2300	3100
Schalldruckpegel		[dB(A)]	54	55
Schalleistungspegel		[dB(A)]	61	62
Abmessungen	netto [mm]	800x315x545	800x315x545	834x328x655
	brutto [mm]	920x400x620	920x400x620	945x435x725
Gewicht netto/brutto		[kg]	34 / 37	36 / 39
Rohranschlüsse	Flüssig [mm(zoll)]	2x 6,35 (1/4)	2x 6,35 (1/4)	3x 6,35 (1/4)
	Gas [mm(zoll)]	2x 9,52 (3/8)	2x 9,52 (3/8)	3x 9,52 (3/8)
Max. Einbaulänge		[m]	25	25
Max. Höhenunterschied		[m]	15	15
Betriebsbereich	Kühlen [°C]	-15~52	-15~52	-15~52
	Heizen [°C]	-15~24	-15~24	-15~24

Modell		SEV-3M27	SEV-4M36	SEV-5M42
Kühlleistung	[kW]	7,9 (2,3 - 8,69)	10,5 (2,5 - 11,0)	12,0 (2,77 - 12,7)
	[Btu/h]	26955 (7848 - 29650)	35826 (8530 - 37532)	40944 (9451 - 43332)
Heizleistung	[kW]	8,2 (2,45 - 9,02)	11,0 (2,67 - 11,2)	13,0 (2,96 - 13,1)
	[Btu/h]	27978 (8359 - 30776)	37532 (9110 - 38214)	44356 (10100 - 44800)
Stromanschluss		[V~,Hz,Ph]	220-240, 50, 1	220-240, 50, 1
Energieverbrauch	Kühlen [W]	2460	3950	4450
	Heizen [W]	2270	3150	3750
Stromverbrauch	Kühlen [A]	10,7	17,5	19,72
	Heizen [A]	9,8	13,96	16,62
SEER		[W/W]	6,30	6,10
SCOP		[W/W]	4,04	4,00
Energieeffizienz	Kühlen [-]	A++	A++	A++
	Heizen [-]	A+	A+	A+
Luftvolumenstrom		[m³/h]	3100	4000
Schalldruckpegel		[dB(A)]	58	61
Schalleistungspegel		[dB(A)]	65	68
Abmessungen	netto [mm]	834x328x655	985x395x808	985x395x808
	brutto [mm]	945x435x725	1105x495x895	1105x495x895
Gewicht netto/brutto		[kg]	46 / 49	74 / 78
Rohranschlüsse	Flüssig [mm(zoll)]	3x 6,35 (1/4)	4x 6,35 (1/4)	5x 6,35 (1/4)
	Gas [mm(zoll)]	3x 9,52 (3/8)	4x 9,52 (3/8)	5x 9,52 (3/8)
Max. Einbaulänge		[m]	30	35
Max. Höhenunterschied		[m]	15	15
Betriebsbereich	Kühlen [°C]	-15~52	-15~52	-15~52
	Heizen [°C]	-15~24	-15~24	-15~24